

A11-S

Radiant metal ceiling sail



QUICK FACTS

- Thermal comfort according to EN ISO 7730
- Very high heating & cooling capacity
- Active area ratio: 85 %
- Superior sound absorption values (class A)
- Easy installation
- Low system weight
- Variable coil design
- Can be combined with ARCHISONIC®, AQUILO, CAURUS
- Integration of various components
 - Different lighting designs
 - Sprinklers
 - Smoke detectors
 - Supply / extract air elements

Output (water)	
Cooling	Heating
Up to 105 W/m ² (8 K), EN 14240:2004	Up to 117 W/m ² (15 K), EN 14037:2016
Acoustics	
α_w : up to 1,00	

Technical description

General

The A11-S radiant ceiling sail is a highly efficient radiant ceiling system that receives a flow of room air on all sides. If a full-surface insulation insert is not installed, the back of the sail can also actively contribute to room cooling.

The innovative A11 activation system has a special structure. The copper pipe and aluminium heat conducting rails are welded together using laser technology. The coils are permanently bonded to the metal plates using a special adhesive and high pressure, thereby ensuring optimum thermal transfer. Aluminium panels can also be activated using the adhesive technology, which results in further improvements in performance.

In order to satisfy the acoustic requirements, acoustic fleece is bonded in the back of the ceiling panels. In particularly sensitive areas, additional insulation strips can be inserted at the side of the coil to increase sound absorption without reducing the cooling capacity.

Activation

Water system: The radiant ceiling is a passive system that in the case of cooling absorbs heat from the room via the ceiling surface, transfers it to the water, which is conducted in activation registers, and dissipates it, respectively emits heat in the case of heating.

The activation of the A11-S radiant metal ceiling system consists of meandering copper pipes (outside diameter 12 mm) and aluminum heat-conducting rails (width 80 mm), which are connected by laser spot welding and glued into the ceiling panels.

Optional performance plus: Convector Wings




Convector Wings are matt black anodized aluminum profiles with slotted «wings» on both sides. With the profile that opens downwards, the Convector Wings can be attached to the straight sections of a pipe meander. This multiplies the heat exchange surface of the radiant ceiling sail, which leads to an increase in water capacity.

Functions

The A11-S radiant metal ceiling sail is multifunctional. In addition to the thermal functions of cooling/heating, there is the possibility of further integration: acoustically effective inserts or baffles (ARCHISONIC®), special supply air solutions (AQUILO, CAURUS), various built-in components (e.g. smoke detectors, lighting).

Combinations

- A11-S radiant metal ceiling sail + ARCHISONIC®
- A11-S radiant metal ceiling sail + AQUILO
- A11-S radiant metal ceiling sail + CAURUS



Optional performance plus: Convector Wings

Technical data


Capacity

Initial data is presented below.


Material ceiling panel	Aluminum	Steel
Perforation	Rg 1,5 – 11 %	Rg 1,5 – 11 %
Distance heat conducting rails (hcr)	100 mm --- ② 150 mm — ③	100 mm + Convector Wings ① 150 mm — ④
Activation method	on fleece	on fleece

(Capacity information without project-specific performance-influencing factors.)

EN 14240:2004



EN 14037:2016



Version	Cooling 8 K	Cooling 10 K	Heating 15 K
① Steel 100 mm + Convector Wings	up to 122 w/m²	up to 148 w/m²	up to 117 w/m² (---·---)
② Aluminum 100 mm	up to 105 w/m²	up to 135 w/m²	up to 117 w/m² (---·---)
③ Aluminum 150 mm	up to 97 w/m²	up to 124 w/m²	up to 110 w/m²
④ Steel 150 mm	up to 83 w/m²	up to 106 w/m²	up to 105 w/m²

Notice

- SN EN 14240: The cooling capacity is related to the active area according to SN EN 14240:2004. The active area is calculated according to SN EN 14240 from the number of heat-conducting rails x length of heat conducting rail x distance between heat conducting rails.
- SN EN 14037: The heating capacity is related to the active area according to SN EN 14037:2016. The active area is calculated according to SN EN 14037 from the length of the ceiling panel x the width of the ceiling panel.

Recommendations for operation

Water

- Temperature
 - Cooling 16 – 18 °C
 - Heating 28 – 37 °C
- Temperature distance Δt (VL-RL): 2 – 3 K
- Pressure drop: 20 – 25 kPa
- Water flow: 80 – 150 l/h
- Max. operating pressure up to 9 bar
- Water quality according to: SWKI BT 102-01, BTGA 3.003, VDI 2035


Surrounding

- Ambient temperatures: +5 – 50 °C
- Humidity: up to 90 % relative humidity

Acoustics

Initial data is presented below.

Perforation	Rg 1,5 – 11 %	Rg 1,5 – 11 %
Distance heat conducting rails (hcr)	150 mm	150 mm
Installation height	200 mm	200 mm
Acoustic inlay	Fleece	Fleece
Additional inlay (mineral wool)	without ———	with - - - -
Sound absorption α_p	250: 0,55 500: 0,90 1k: 0,75 2k: 0,75 4k: 0,65	250: 1,00 500: 1,00 1k: 1,00 2k: 1,00 4k: 0,90
Sound absorption α_w	α_w : 0,75	α_w : 1,00
Sound absorption class (EN ISO 11654)	C	A



System

Ceiling system

- Sail
 - Square and rectangular panels
 - Special solutions on request

Installation systems

- Installation high: min. 80 mm
 - Hook-on system
 - Threaded rods or ropes

Materials, weight and dimensions

Materials and weight

Material	Weight (incl. activation, water)
Aluminum 1,00 mm	3,5 – 6,0 kg/m ²
Steel 0,70 mm	6,26 – 8,58 kg/m ²

Building material class: A2-s1, d0, EN 13501-1 (depending on the acoustic solution).

Dimensions

Panel length	Panel width	Panel height
min. 800 mm	min. 400 mm	min. 30 mm
max. 3000 mm	max. 1200 mm	max. 50 mm

Special dimensions on request.

Surface

Versions

- Powder coating
- Digital printing on request

Colors


- Standard RAL 9010
- Other RAL / NCS colors on request

Perforations


- Standard perforations
- Other perforations on request

Standard perforations:


Rd 1,5 – 11 %




Rg 1,5 – 11 %



Rd 1,5 – 22 %



Rg 2,5 – 16 %



International

Barcol-Air Group AG

Wiesenstrasse 5
8603 Schwerzenbach
T +41 58 219 40 00
F +41 58 218 40 01
info@barcolair.com

Switzerland



Barcol-Air AG

Wiesenstrasse 5
8603 Schwerzenbach
T +41 58 219 40 00
F +41 58 218 40 01
info@barcolair.com

Barcol-Air AG

Via Bagutti 14
6900 Lugano
T +41 58 219 45 00
F +41 58 219 45 01
ticino@barcolair.com

Germany

Swegon Klimadecken GmbH

Schwarzwaldstrasse 2
64646 Heppenheim
T: +49 6252 7907-0
F: +49 6252 7907-31
klimadecken@swegon.de
swegon.de/klimadecken

France

Barcol-Air France SAS

Parc Saint Christophe
10, avenue de l'Entreprise
95861 Cergy-Pontoise Cedex
T +33 134 24 35 26
F +33 134 24 35 21
france@barcolair.com

Italy

Barcol-Air Italia S.r.l.

Via Leone XIII n. 14
20145 Milano
T +41 58 219 45 40
F +41 58 219 45 01
italia@barcolair.com